

# XTS6000 LCD Touch Monitor

# POSX

[www.pos-x.com](http://www.pos-x.com)



POINT OF SALE PERFECTED

Optimized for retail and hospitality environments, the 15" XTS6000 LCD touch monitor combines stability and durability with resistive touch technology to streamline ordering and payments at the point of sale. Built to last, the XTS6000 touch monitor is backed with a 3-year warranty.

- ◆ Slim panel design fits most spaces
- ◆ Low power consumption
- ◆ Adjustable 160-degree tilting angle
- ◆ Bright, high-resolution LCD display
- ◆ Sturdy base with built-in cable management
- ◆ 5-wire resistive touch technology

## Display

LCD Panel	15" TFT LCD Active Matrix Display
Resolution	1024 x 768 pixel, 16.7M colors
Contrast Ratio	400:1
Brightness	250 cd/m2
Pixel Pitch	0.297 mm x 0.297 mm
On Screen Control	Auto tune, brightness, contrast, clock, phase, H-position, V-position, recall
Display Mode	VGA 720 x 400, VGA 640 x 480, SVGA 800 x 600, XGA 1024 x 768
Viewing Angle	-75"/+75" L to R; -70"/+70" Up & Down
Scan Rate	30 - 60 KHz (horizontal)
	56 - 75 KHz (vertical)

## Touch Specs

Technology	5 Wire Resistive
Interface	USB
Touch Active Area	11.95" x 8.96"

## Safety & Regulatory Approvals

FCC, CE, MIC, UL Compliant
Plug and Play DDC 2B Compliance

## Models

XTS6000U	XTS6000U w/ USB Interface
----------	---------------------------



## Power

Consumption	30 Watts (max)
Adapter Input	100-240 VAC, 50-60Hz 1.5A
Adapter Output	12 VDC, 3.33A (C+)

## Environmental

Temperature	32° - 104°F (operating)
	-4° - 140°F (storage)
Humidity	10% - 80% non-condensing (operating)
	10% - 90% non-condensing (storage)

## Physical

Weight	13.9 lbs.
Dimensions	13.5" x 14.3" x 7.3" (W x H x D)
Color	Black
Front Controls	Power on/off with LED, menu, auto tune, adjustment (+/-)
Stand Style	PED -3 Cable Management Base
Mounting Options	Desktop placement, bolt down & VESA mountable
Monitor Tilting Angle	160°
PC Video Interface	Analog RGB (VGA)

## Warranty

3-Year Limited Warranty
-------------------------